



420 Highland Ave. Ext, Middletown, N.Y. 10940
 Office: 845-360-5363 | Toll Free: 800-781-8027 | Fax: 775-255-3044
 © RTG Lighting, Inc. | sales@rtglighting.com

GP950 Series LED

General Purpose



PROJECT INFORMATION

Project Name	Type
Catalog No	Date

DESCRIPTION


The GP-LED-950 Series Industrial LED fixture's versatile design makes it compatible for use as a pole mounted Shoebox, Flood Light, or Area Light based on the mounting type used.

The GP-LED-950 Series fixture can be widely used in outdoor lighting, such as parking lots, Tunnel Lighting, gas stations, toll booth, platforms of railway station or stadium lighting.

FEATURES

- Die-cast aluminum housing with excellent heat dissipation. Powder coat finish for corrosion and static resistance.
- Optical grade polycarbonate lens.
- Photocell Available
- LED module can be dismantled separately for maintenance.
- 50,000 Burning Hours.
- IP65
- DLC Listed

DIMENSIONS



WARRANTY

5 years

Example

GP950 150w 19500 lm - 2700k MV SF 10V Bronze

ORDERING INFORMATION

GP950	Watts / Lumens / Length	Color Temp	Voltage	Mounts	Options	Finish Options
	150w 19500 Lm -	2700K, 3000K	100-277V (MV)	Slipfitter (SF)	0-10V Dimming (10V)	Bronze
	200w 26000 Lm -	4000K, 5000K		Straight Arm (SA)	Timing Dimming (TDim)	
	240w 31200 Lm -	5700K		U-Mount (UM)	Photocell (PC)	
	300w 39000 Lm -					